

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

Print date: 2025/01/01
Version: 6.1



SealBoss 15X Accelerator
Revision date: 2025/01/01
Issue date: 2025/01/01

EN
Page 1 / 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier
Trade name/designation SealBoss 15X Accelerator
PU Injection Foam Resin
- 1.2. Relevant identified uses of the substance or mixture and uses advised against
Relevant identified uses
polyhydroxy alcohol - amine component for polyurethane foam resin
- 1.3. Details of the supplier of the safety data sheet
supplier (manufacturer/importer/downstream user/distributor)
SealBoss Corp Telephone: + 1 (714)-662-4445
1669 E Wilshire Ave Ste 609 Telefax: + 1(714)662-444 6
Santa Ana, CA 92705
USA
Department responsible for information:
laboratory
E-mail info@sealboss.com
- 1.4. Emergency telephone number
ChemTel 1-800-255-3924 OR International: +01-813-248-0585

SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture
Classification according to Regulation (EC) No 1272/2008 [CLP]
The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP].
Skin Irrit. 2 / H315 Skin corrosion/irritation Causes skin irritation.
Eye Dam. 1 / H318 Serious eye damage/eye irritation Causes serious eye damage.
Skin Sens. 1 / H317 Respiratory or skin sensitisation May cause an allergic skin reaction.
- 2.2. Label elements
Labelling according to Regulation (EC) No. 1272/2008 [CLP]
Hazard pictograms
  Danger
Hazard statements
H315 Causes skin irritation.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.
Precautionary Statements
P 280 Wear protective gloves and eye/face protection.
P 305 + P 351 + P 338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P 310 Immediately call a POISON CENTER or doctor/ physician.
Hazard components for labelling
2-[2-(dimethylamino)ethoxy]ethanol
N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine
Supplemental hazard information
not applicable
- 2.3. Other hazards
No information available.

SECTION 3: Composition / information on ingredients

- 3.2. Mixtures
Description polyhydroxy alcohol - amine component for polyurethane foam resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

Print date: 2025/01/01
Version: 6.1

SealBoss 15X Accelerator
Revision date: 2025/01/01
Issue date: 2025/01/01

EN
Page 2 / 8

Hazardous ingredients

EC No.	REACH No.	weight-%
CAS No.	Designation	
INDEX No.	classification: // Remark	
216-940-1 1704-62-7	01-2119976346-26-xxxx 2-[2-(dimethylamino)ethoxy]ethanol Acute Tox. 4 H312 / Skin Corr. 1C H314	2,5 - 10
470-720-1 189253-72-3	01-0000019735-62-xxxx N-(2-(dimethylamino)ethoxy)ethyl)-N-methyl-1,3-propanediamine Acute Tox. 4 H302 / Skin Corr. 1B H314 / Eye Dam. 1 H318 / Skin Sens. 1 H317	1 - 2,5

Additional information

Full text of classification: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

In case of inhalation

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

Following skin contact

Take off immediately all contaminated clothing. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

In all cases of doubt, or when symptoms persist, seek medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

Unsuitable extinguishing media

strong water jet

5.2. Special hazards arising from the substance or mixture

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

5.3. Advice for firefighters

Provide a conveniently located respiratory protective device. Do not allow water used to extinguish fire to enter drains, ground or waterways.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Ventilate affected area. Do not breathe vapours.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

6.3. Methods and material for containment and cleaning up

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

Print date: 2025/01/01
Version: 6.1

SealBoss 15X Accelerator
Revision date: 2025/01/01
Issue date: 2025/01/01

EN
Page 3 / 8

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see section 13).

- 6.4. Reference to other sections
Observe protective provisions (see section 7 and 8).

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advices on safe handling

Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. When using do not eat, drink or smoke. Personal protection equipment: refer to section 8. Follow the legal protection and safety regulations.

Further information

Vapours are heavier than air.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Always keep in containers that correspond to the material of the original container.

Hints on joint storage

Keep away from food, drink and animal feedingstuffs.

Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 5 °C and 30 °C. Protect from heat and direct sunlight.

7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limit values:

not applicable

DNEL:

2-[2-(dimethylamino)ethoxy]ethanol

EC No. 216-940-1 / CAS No. 1704-62-7

DNEL long-term dermal (systemic), Workers: 2,33 mg/kg bw/day

DNEL long-term inhalative (local), Workers: 1,07 mg/m³

DNEL long-term inhalative (systemic), Workers: 0,48 mg/m³

PNEC:

2-[2-(dimethylamino)ethoxy]ethanol

EC No. 216-940-1 / CAS No. 1704-62-7

PNEC aquatic, freshwater: 0,1 mg/L

PNEC aquatic, marine water: 0,01 mg/L

PNEC aquatic, intermittent release: 1 mg/L

PNEC sediment, freshwater: 8,6957 x10⁻² mg/kg

PNEC sediment, marine water: 0,8696 x10⁻² mg/kg

PNEC, soil: 2,8174 x10⁻² mg/kg

PNEC sewage treatment plant (STP): 100 mg/L

N-(2-(dimethylamino)ethoxy)ethyl-N-methyl-1,3-propanediamine

EC No. 470-720-1 / CAS No. 189253-72-3

PNEC aquatic, freshwater: 0,15 mg/L

PNEC aquatic, marine water: 0,015 mg/L

PNEC aquatic, intermittent release:

PNEC sediment, freshwater: 0,54 mg/kg

PNEC sediment, marine water: 0,054 mg/kg

PNEC sewage treatment plant (STP): 10 mg/L

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

Print date: 2025/01/01
Version: 6

SealBoss 15X Accelerator
Revision date: 2025/01/01
Issue date: 2025/01/01

EN
Page 4 / 8

8.2. Exposure controls

Provide good ventilation. This can be achieved with local or room suction. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means. In case of inadequate ventilation wear respiratory protection.

Personal protection equipment

Respiratory protection

Suitable respiratory protection apparatus:

Usually no personal respiratory protection necessary.

Hand protection

For prolonged or repeated handling the following glove material must be used: nitrile rubber or butyl rubber

Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.

Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles EN ISO 374

Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Eye/face protection

Wear eye glasses with side protection according to EN 166.

Body protection

Wear suitable protective clothing.

Protective measures

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

Environmental exposure controls

Do not allow to enter into surface water or drains. See section 7. No additional measures necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance:

Physical state: Liquid
Colour: yellow

Odour: characteristic

Odour threshold: not determined

pH at 20 °C: not applicable

Melting point/freezing point: not determined

Initial boiling point and boiling range: not determined

Flash point: > 101 °C
Method: DIN 53213

flammability

Burning time (s): not applicable

Upper/lower flammability or explosive limits:

Lower explosion limit: not determined

Upper explosion limit: not determined

Vapour pressure at 20 °C: 0,3365 mbar
Method: calculated

Relative density:

Density at 20 °C: 0,96 g/cm³
Method: calculated

Solubility(ies):

Water solubility (g/L) at 20 °C: insoluble

Partition coefficient: n-octanol/water: see section 12

Auto-ignition temperature: not determined

Decomposition temperature: not applicable

Viscosity at 40 °C: > 20,5 mm²/s

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

Print date: 2025/01/01
Version: 6

SealBoss 15X Accelerator
Revision date: 2025/01/01
Issue date: 2025/01/01

EN
Page 5 / 8

Explosive properties:	not applicable
Oxidising properties:	not applicable
9.2. Other information	
Solvent	
Organic solvents:	0 weight-%

SECTION 10: Stability and reactivity

- 10.1. Reactivity
No information available.
- 10.2. Chemical stability
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.3. Possibility of hazardous reactions
Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.
- 10.4. Conditions to avoid
Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to section 7.
- 10.5. Incompatible materials
not applicable
- 10.6. Hazardous decomposition products
Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

SECTION 11: Toxicological information

- Classification according to Regulation (EC) No 1272/2008 [CLP]
No data on preparation itself available.
- 11.1. Information on toxicological effects
- Acute toxicity
- 2-[2-(dimethylamino)ethoxy]ethanol
oral, LD50, Rat: 2460 mg/kg
dermal, LD50, Rabbit: 1410 mg/kg
- N-(2-(dimethylamino)ethoxy)ethyl-N-methyl-1,3-propanediamine
oral, LD50, Rat: > 1000 mg/kg
- Skin corrosion/irritation; Serious eye damage/eye irritation
- Causes skin irritation.
- Causes serious eye damage.
- Respiratory or skin sensitisation
- May cause an allergic skin reaction.
- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)
Based on available data, the classification criteria are not met.
- STOT-single exposure; STOT-repeated exposure
Based on available data, the classification criteria are not met.
- Aspiration hazard
Based on available data, the classification criteria are not met.
- Practical experience/human evidence
No information available.
- Overall Assessment on CMR properties
The ingredients in this mixture do not meet the criteria for classification as CMR category 1A or 1B according to CLP.

SECTION 12: Ecological information

- Classification according to Regulation (EC) No 1272/2008 [CLP]
There is no information available on the preparation itself.

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

Print date: 2025/01/01
Version: 6.1

SealBoss 15X Accelerator
Revision date: 2025/01/01
Issue date: 2025/01/01

EN
Page 6 / 8

Do not allow to enter into surface water or drains.

12.1. Toxicity

N-(2-(dimethylamino)ethoxy)ethyl-N-methyl-1,3-propanediamine
Fish toxicity, LC50, Cyprinus carpio (Common Carp): > 100 mg/L (96 h)
Daphnia toxicity, EC50, Daphnia magna (Big water flea): > 100 mg/L (48 h)
Algae toxicity, ErC50, Selenastrum capricornutum: 64 mg/L (72 h)

Long-term Ecotoxicity

N-(2-(dimethylamino)ethoxy)ethyl-N-methyl-1,3-propanediamine
Algae toxicity, NOEC, Pseudokirchneriella subcapitata: 32 mg/L (72 h)

12.2. Persistence and degradability

Toxicological data are not available.

12.3. Bioaccumulative potential

Toxicological data are not available.

Bioconcentration factor (BCF)

Toxicological data are not available.

12.4. Mobility in soil

Toxicological data are not available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Appropriate disposal / Product
Recommendation

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Dispose of waste according to applicable legislation.

List of proposed waste codes/waste designations in accordance with EWC
070208* other still bottoms and reaction residues

*Hazardous waste according to Directive 2008/98/EC (waste framework directive).

Appropriate disposal / Package
Recommendation

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

SECTION 14: Transport information

No dangerous good in sense of this transport regulation.

14.1. UN number

not applicable

14.2. UN proper shipping name

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

Land transport (ADR/RID)

not applicable

Marine pollutant

not applicable

14.6. Special precautions for user

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

Print date: 2025/01/01
Version: 6.1

SealBoss 15X Accelerator
Revision date: 2025/01/01
Issue date: 2025/01/01

EN
Page 7 / 8

Further information

Land transport (ADR/RID)

tunnel restriction code -

Sea transport (IMDG)

EmS-No. not applicable

Air transport (ICAO-TI / IATA-DGR)

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Directive 2010/75/EU on industrial emissions

VOC-value (in g/L): 0,000

National regulations

Restrictions of occupation

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Full text of classification in section 3:

Acute Tox. 4 / H312	Acute toxicity (dermal)	Harmful in contact with skin.
Skin Corr. 1C / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Acute Tox. 4 / H302	Acute toxicity (oral)	Harmful if swallowed.
Skin Corr. 1B / H314	Skin corrosion/irritation	Causes severe skin burns and eye damage.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	Causes serious eye damage.
Skin Sens. 1 / H317	Respiratory or skin sensitisation	May cause an allergic skin reaction.

Classification procedure

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Skin Irrit. 2	Skin corrosion/irritation	Calculation method.
Eye Dam. 1	Serious eye damage/eye irritation	Calculation method.
Skin Sens. 1	Respiratory or skin sensitisation	Calculation method.

Abbreviations and acronyms

ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
OEL	Occupational Exposure Limit Value
BLV	Biological Limit Value
CAS	Chemical Abstracts Service
CLP	Classification, Labelling and Packaging
CMR	Carcinogenic, Mutagenic and Reprotoxic
DIN	German Institute for Standardization / German industrial standard
DNEL	Derived No-Effect Level
EAKV	European Waste Catalogue Directive
EC	Effective Concentration
EC	European Community
EN	European Standard
IATA-DGR	International Air Transport Association – Dangerous Goods Regulations
IBC Code	International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk
ICAO-TI	International Civil Aviation Organization Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG Code	International Maritime Code for Dangerous Goods
ISO	International Organization for Standardization
LC	Lethal Concentration
LD	Lethal Dose

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH)

according to Regulation (EU) 2015/830

Print date: 2025/01/01
Version: 6.1

SealBoss 15X Accelerator
Revision date: 2025/01/01
Issue date: 2025/01/01

EN
Page 8 / 8

MARP OL	Maritime Pollution: The International Convention for the Prevention of Pollution from Ships
OECD	Organisation for Economic Cooperation and Development
PBT	persistent, bioaccumulative, toxic
PNEC	Predicted No Effect Concentration
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
UN	United Nations
VOC	Volatile Organic Compounds
vPvB	very persistent and very bioaccumulative

Further information

Classification according to Regulation (EC) No 1272/2008 [CLP]

Limited Warranty Policy and Disclaimer for Products Supplied and/or Distributed by SealBoss Corp.: All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instruction for each product as set forth in the current Technical Data Sheet, product label and Material Safety Data Sheet prior to product use. SealBoss Corp. warrants supplied / distributed products to be free of manufacturing defects. Seller's and manufacturer's sole responsibility shall be to replace that portion of the product of the manufacturer which proves to be defective. There are no other warranties by SealBoss Corp. of any nature whatsoever expressed or implied, including any warranty of merchantability or fitness for a particular purpose in connection with this product. SealBoss Corp. shall not be liable for damages of any sort, including remote or consequential damages resulting from any claimed breach of any warranty whether expressed or implied. SealBoss Corp. shall not be responsible for use of this product in a manner to infringe on any patent or any other intellectual property rights held by others. In addition, no warranty or guarantee is being issued with respect to appearance, color, fading, chalking, staining, shrinkage, peeling, UV damage, excessive temperature exposure, normal wear and tear or improper application by the applicator. Damage caused by abuse, neglect and lack of proper maintenance, acts of nature and / or physical movement of the substrate or structural defects are also excluded from the limited warranty. SealBoss Corp. reserves the right to conduct performance tests on any material claimed to be defective prior to any repairs by owner, general contractor, or applicator. Neither seller nor manufacturer shall be liable to the buyer or any third person for any injury, loss or damage directly or indirectly resulting from use of or inability to use the product. Recommendations and statements other than those contained in a written agreement signed by an officer of the manufacturer shall not be binding upon the manufacturer or seller. SealBoss Corp. reserves the right to change the properties of products without notice.