

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK HIGH TACK FAST WHITE Supercedes Date: 20-Dec-2022

Revision date 20-Dec-2022

Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK HIGH TACK FAST WHITE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

2.2. Label elements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

Signal word

None

Hazard statements

This mixture is classified as not hazardous according to regulation (EC) 1272/2008 [CLP]

EU Specific Hazard Statements

EUH208 - Contains Trimethoxyvinylsilane. May produce an allergic reaction

EUH210 - Safety data sheet available on request

2.3. Other hazards

United Kingdom - BE Page 1 / 14

BOSTIK HIGH TACK FAST WHITE Supercedes Date: 20-Dec-2022 Revision date 20-Dec-2022 Revision Number 1

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon curing. Harmful to aquatic life.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Trimethoxyvinylsilane	(014-049-00- 0) 220-449-8	2768-02-7	1 - <3	Skin Sens. 1B (H317) Acute Tox. 4 (H332) Flam. Liq. 3 (H226)	-	01-2119513215- 52-XXXX
Titanium dioxide	(022-006-00- 2) 236-675-5	13463-67-7	0.1- <1	[C]	-	01-2119489379- 17-XXXX
Bis(2,2,6,6-tetramethyl-4 -piperidyl) sebacate	258-207-9	52829-07-9	0.1 - <0.5	Eye Dam. 1 (H318) Repr. 2 (H361f) Aquatic Acute 1 (H400) Aquatic Chronic 2 (H411)	-	01-2119537297- 32-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice Show this safety data sheet to the doctor in attendance. If medical advice is needed,

have product container or label at hand.

Inhalation Remove to fresh air. If symptoms persist, call a doctor.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

Skin contact In the case of skin irritation or allergic reactions see a doctor. Wash skin with soap and

United Kingdom - BE Page 2 / 14

BOSTIK HIGH TACK FAST WHITE
Supercedes Date: 20-Dec-2022
Revision Number 1

water.

Ingestion Call a doctor immediately. Rinse mouth thoroughly with water. Never give anything by

mouth to an unconscious person. Small amounts of toxic methanol are released by

hydrolysis.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms None known.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors

Treat symptomatically. Small amounts of methanol (CAS 67-56-1) are formed by

hydrolysis and released upon curing.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous combustion products Carbon oxides. Carbon monoxide. Carbon dioxide (CO2). Nitrogen oxides (NOx). Silicon

dioxide. Thermal decomposition can lead to release of irritating and toxic gases and

vapours.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Use personal protective equipment as required. Ensure adequate ventilation. Do not get

in eyes, on skin, or on clothing.

Other information Prevent further leakage or spillage if safe to do so.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil. See Section

12 for additional Ecological Information.

6.3. Methods and material for containment and cleaning up

Methods for containmentDo not scatter spilled material with high pressure water streams.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

United Kingdom - BE Page 3/14

Revision date 20-Dec-2022

Revision Number 1

BOSTIK HIGH TACK FAST WHITE
Supercedes Date: 20-Dec-2022

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Ensure adequate ventilation.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Protect from moisture. Keep away from food, drink and animal feedingstuffs.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing This product contains titanium dioxide in a non-respirable form. Inhalation of

titanium dioxide is unlikely to occur from exposure to this product

Chemical name	European Union	United Kingdom
Limestone	-	TWA: 10 mg/m ³
1317-65-3		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³
Methyl alcohol	TWA: 200 ppm	TWA: 200 ppm
67-56-1	TWA: 260 mg/m ³	TWA: 266 mg/m ³
	*	STEL: 250 ppm
		STEL: 333 mg/m ³
		Sk*
Titanium dioxide	-	TWA: 10 mg/m ³
13463-67-7		TWA: 4 mg/m ³
		STEL: 30 mg/m ³
		STEL: 12 mg/m ³

Chemical name	European Union	Ireland	United Kingdom
Methyl alcohol	-	15 mg/L (urine - Methanol end of	-
67-56-1		shift)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)					
Trimethoxyvinylsilane (2768-02-7)					
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor		
worker	Inhalation	27,6 mg/m³			

United Kingdom - BE Page 4 / 14

BOSTIK HIGH TACK FAST WHITE Revision date 20-Dec-2022 Supercedes Date: 20-Dec-2022 **Revision Number** 1 Systemic health effects Long term worker Dermal 3,9 mg/kg bw/d Systemic health effects Long term Titanium dioxide (13463-67-7) Derived No Effect Level Safety factor Type Exposure route (DNEL) worker Inhalation 10 mg/m³ Long term Local health effects Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9) Derived No Effect Level Type Exposure route Safety factor (DNEL) Inhalation 2.82 mg/m³ worker Short term Long term Systemic health effects Dermal 1.6 mg/kg worker Long term Systemic health effects Derived No Effect Level (DNEL) Trimethoxyvinylsilane (2768-02-7) Derived No Effect Level Type Exposure route Safety factor (DNEL) Consumer Inhalation 18,9 mg/m³ Systemic health effects Long term Consumer Dermal 7,8 mg/kg bw/d Systemic health effects ong term Oral 0,3 mg/kg bw/d Consumer Systemic health effects Long term Titanium dioxide (13463-67-7) Derived No Effect Level Type Exposure route Safety factor (DNEL) Oral 700 mg/kg bw/d Consumer Long term Systemic health effects Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9) Derived No Effect Level Type Exposure route Safety factor (DNEL) Consumer Dermal 0.8 mg/kg

Predicted No Effect Concentration No information available. **(PNEC)**

Oral

Long term

Consumer

Long term

Systemic health effects

Systemic health effects

United Kingdom - BE Page 5 / 14

0.4 mg/kg

BOSTIK HIGH TACK FAST WHITE Supercedes Date: 20-Dec-2022

Revision date 20-Dec-2022 Revision Number 1

Predicted No Effect Concentration (PNEC)	
Trimethoxyvinylsilane (2768-02-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.34 mg/l
Marine water	0.034 mg/l
Microorganisms in sewage treatment	110 mg/l

Titanium dioxide (13463-67-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Marine water	0.0184 mg/l
Freshwater sediment	1000 mg/kg
Freshwater	0.184 mg/l
Marine sediment	100 mg/kg
Soil	100 mg/kg
Microorganisms in sewage treatment	100 mg/l
Freshwater - intermittent	0.193 mg/l

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.018 mg/l
Marine water	0.0018 mg/l
Freshwater sediment	29 mg/kg
Marine sediment	2.9 mg/kg
Soil	5.9 mg/kg

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas.

Personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Neoprene™. Nitrile rubber. Butyl rubber.

Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

gloves. Gloves must conform to standard EN 374

Skin and body protection Respiratory protection

None under normal use conditions.

In case of inadequate ventilation wear respiratory protection. Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Recommended filter type: Organic gases and vapours filter conforming to EN 14387. White. Brown.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state Solid
Appearance Paste
Colour White

Odour No information available.
Odour threshold No information available

Property Values Remarks • Method

Melting point / freezing pointNo data availableNone knownInitial boiling point and boilingNo data availableNone known

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

limits

United Kingdom - BE Page 6 / 14

Revision date 20-Dec-2022

Revision Number 1

BOSTIK HIGH TACK FAST WHITE Supercedes Date: 20-Dec-2022

Lower flammability or explosive No data available

limits

Flash point > 60 °C None known Autoignition temperature No data available None known

Decomposition temperature None known

pHNo data availableNone known.pH (as aqueous solution)No data availableNone knownKinematic viscosity> 21 mm²/sNone known

Dynamic viscosity

Water solubility

No data available Insoluble in water.

Solubility(ies)No data availableNone knownPartition coefficientNo data availableNone knownVapour pressureNo data availableNone knownRelative densityNo data availableNone known

Bulk Density

No data available

No data available

1.56 g/cm³

Relative vapour density No data available None known

Particle characteristics

Particle SizeNo information availableParticle Size DistributionNo information available

9.2. Other information

Solid content (%) No information available

VOC content No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Product cures with moisture.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid Protect from moisture. Exposure to air or moisture over prolonged periods. Do not freeze.

Keep away from open flames, hot surfaces and sources of ignition.

10.5. Incompatible materials

Incompatible materialsNone known based on information supplied.

10.6. Hazardous decomposition products

United Kingdom - BE Page 7 / 14

BOSTIK HIGH TACK FAST WHITE Supercedes Date: 20-Dec-2022

Revision Number 1

Revision date 20-Dec-2022

Hazardous decomposition

products

Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released upon

curing.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Based on available data, the classification criteria are not met. May cause sensitisation in

susceptible persons.

Ingestion Based on available data, the classification criteria are not met.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Acute toxicity

Numerical measures of toxicity

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (inhalation-vapour) 377.70 mg/l

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Trimethoxyvinylsilane	LD50 = 7120 - 7236 mg/kg	= 3540 mg/kg (Oryctolagus	LC50 (4hr) 16.8 mg/l (Rattus)
	(Rattus) OECD 401	cuniculus)	OECD TG 403
Titanium dioxide	>10000 mg/kg (Rattus)	LD50 > 5000 mg/Kg	= 5.09 mg/L (Rattus) 4 h
Bis(2,2,6,6-tetramethyl-4-piperi dyl) sebacate	LD50 (Rattus)> 2000 mg/kg OECD 423	LD50 (Rattus) > 3 170 mg/kg OECD 402	=500 mg/m³ (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit		0.5 mL	24 hours	Non-irritant

Titanium dioxide (13463-67-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404:	Rabbit	Dermal			Non-irritant
Acute Dermal					
Irritation/Corrosion					

Method	Species	Exposure route	Effective dose	Exposure time	Results
·					

United Kingdom - BE Page 8 / 14

BOSTIK HIGH TACK FAST WHITE Revision date 20-Dec-2022 Supercedes Date: 20-Dec-2022 **Revision Number 1** OECD Test No. 404: Rabbit Dermal Non-irritant Acute Dermal Irritation/Corrosion Serious eye damage/eye irritation Based on available data, the classification criteria are not met. Trimethoxyvinylsilane (2768-02-7) Method Species **Exposure route** Effective dose **Exposure time** Results OECD Test No. 405: Rabbit eye 24 hours Non-irritant Acute Eye Irritation/Corrosion Titanium dioxide (13463-67-7) Method **Species Exposure route** Effective dose **Exposure time** Results OECD Test No. 405: Rabbit Eye Non-irritant Acute Eye Irritation/Corrosion Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)Results Method Species Exposure route Effective dose Exposure time OECD Test No. 405: Rabbit Eye Damage eye Acute Eye Irritation/Corrosion OECD Test No. 406: Skin Sensitisation. No sensitisation responses were observed. No Respiratory or skin sensitisation classification is proposed, based on conclusive negative data. May cause sensitisation in susceptible persons. Exposure route Method **Species** Results OECD Test No. 406: Skin No sensitisation responses Dermal Guinea pig Sensitisation were observed Trimethoxyvinylsilane (2768-02-7) Method Species Exposure route Results OECD Test No. 406: Skin Guinea pig Dermal sensitising Sensitisation, Buehler test Titanium dioxide (13463-67-7) Method **Species Exposure route** Results OECD Test No. 406: Skin Guinea pig Dermal Not a skin sensitiser Sensitisation OECD Test No. 429: Skin Mouse Dermal Not a skin sensitiser Sensitisation: Local Lymph Node Assay Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9) Species Exposure route Method Results OECD Test No. 406: Skin No sensitisation responses Guinea pig Sensitisation were observed Based on available data, the classification criteria are not met. Germ cell mutagenicity Component Information Trimethoxyvinylsilane (2768-02-7) Method Results Species OECD Test No. 471: Bacterial Reverse in vitro Not mutagenic

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Mutation Test

United Kingdom - BE Page 9 / 14

Revision date 20-Dec-2022

Revision Number 1

BOSTIK HIGH TACK FAST WHITE Supercedes Date: 20-Dec-2022

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Results
OECD Test No. 422: Combined Repeated Dose	Rat	Not Classifiable
Toxicity Study with the		
Reproduction/Developmental Toxicity Screening		
Test		

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Species	Results
OECD Test No. 414: Pre-natal Development	Rat, Rabbit	reproductive toxicant
Toxicity Study		

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Trimethoxyvinylsilane (2768-02-7)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 413:	Rat	Inhalation vapour		90 days	0.058 NOAEL
Sub-chronic Inhalation		·			
Toxicity: 90-day Study					

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life.

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Trimethoxyvinylsilane	EC 50 (72h) >	LC50 (96h) =	-	EC50(48hr)		
2768-02-7	957 mg/l	191 mg/l		168.7mg/l		
	(Desmodesmus	(Oncorhynchus		(Daphnia		
	subspicatus)	mykiss)		magna)		
	EU Method C.3			·		

United Kingdom - BE Page 10 / 14

BOSTIK HIGH TACK FAST WHITE Supercedes Date: 20-Dec-2022 Revision date 20-Dec-2022

Revision Number 1

Titanium dioxide	LC50 (96h)	-	-	-	
13463-67-7	>10000 mg/l				
	(Cyprinodon				
	variegatus)				
	OECD 203				
Bis(2,2,6,6-tetramethyl-	EC50 72Hr	LC50 (96h) =	-	LC50 48Hr 8.58	
4-piperidyl) sebacate	0.705 mg/l	5.29 mg/l		mg/l (Daphnia	
52829-07-9	(Pseudokirchner	(Oryzias latines)		magna)	

12.2. Persistence and degradability

Persistence and degradability No information available.

ella subcapitata)

Trimethoxyvinylsilane (2768-02-7)

Method	Exposure time	Value	Results	
OECD Test No. 301F: Ready	28 days	BOD	51 % Not readily	
Biodegradability: Manometric			biodegradable	
Respirometry Test (TG 301 F)				

Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate (52829-07-9)

Method	Exposure time	Value	Results
OECD Test No. 303: Simulation Test	28 days	Total organic carbon (TOC)	24 % Moderate
- Aerobic Sewage Treatment A:	-		
Activated Sludge Units: B: Biofilms			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Trimethoxyvinylsilane	1.1
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	0.35

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment No information available.

Chemical name	PBT and vPvB assessment
Trimethoxyvinylsilane	The substance is not PBT / vPvB
Titanium dioxide	The substance is not PBT / vPvB PBT assessment does
	not apply
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate	The substance is not PBT / vPvB

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

United Kingdom - BE Page 11 / 14

BOSTIK HIGH TACK FAST WHITE
Supercedes Date: 20-Dec-2022
Revision Number 1

13.1. Waste treatment methods

Waste from residues/unused Di

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Handle contaminated packages in the same way as the product itself.

European Waste Catalogue 08 04 10 waste adhesives and sealants other than those mentioned in 08 04 09

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

IMDG

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Marine pollutantNP

14.6 Special Provisions None

14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

United Kingdom - BE Page 12/14

BOSTIK HIGH TACK FAST WHITE Supercedes Date: 20-Dec-2022

Revision date 20-Dec-2022 Revision Number 1

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

H226 - Flammable liquid and vapour

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H332 - Harmful if inhaled

H361f - Suspected of damaging fertility

H400 - Very toxic to aquatic life

H411 - Toxic to aquatic life with long lasting effects

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 20-Dec-2022

Indication of changes

United Kingdom - BE Page 13/14

BOSTIK HIGH TACK FAST WHITE
Supercedes Date: 20-Dec-2022
Revision Number 1

Revision note SDS sections updated, 3, 8.

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 14/14