

FS-600 high strength flooring adhesive

DATA SHEET



Product Description

FS-600 is the ULTIMATE high solids synthetic rubber spray-grade flooring adhesive in a canister system. Developed for versatility, with a long open time and high tack level, giving good bond strength for a wide range of materials. Particularly suitable for spot sticking carpet tile (except PVC backed) and for perimeter fixing of rubber foam backed carpets.

Suitable for use on most common subfloors. *Not recommended for use on fully flexible vinyls.*

FS-600 is designed to make the installers life easy.... you can forget about having to kneel down and laboriously spread adhesive.... **Flexispray** allows you to **stand and spray**. This will **reduce knee injury** and **reduce labour time and increase efficiency**, in turn bringing you **more profitability**.



Benefits of canister delivery

- > Quick drying with an extended open time
- > Easy to apply while standing, no trowelling whilst on your knees
- > Portable, take anywhere
- > No outside power source required
- > Adjustable spray pattern
- > Non-flammable adhesive
- > High solids formula
- > Up to 300sqm coverage
- > Excellent bond adhesion for a variety of materials including hessian and rubber backed carpets and carpet tiles.
- > Tenacious bond strength
- > Low odour
- > Reduced clean up time

Subfloor Preparation

- > Self levelling compounds
- > Plywood (underlayment grade)
- > Hardboard
- > Existing non-cushion backed resilient floors (must be well bonded, sound, smooth, and free of all waxes, finishes, strippers and cleaners)
- > All paint, varnish, oil, wax and any other finishes that may inhibit good bond should be removed. Repair all joints and cracks with a latex based levelling compound.

Directions for Use

SHAKE WELL BEFORE USE. The installations site must be acclimated with HVAC in operation. Sub-floor preparation, moisture and alkalinity testing must comply with industry standards, and floor-covering manufacturer's guidelines. The floor and room temperature, as well as the flooring materials must be maintained at 18°C to 35°C and the humidity below 65% for 48 hours prior to during and after the testing and installation.

Hold spray gun tip approx. 6-8 inches from the surface to be covered, apply even coats. Do not allow it to concentrate or puddle in one area.

Disposal of canisters: Canisters may be recycled or disposed of in accordance with local Council regulations.

IMPORTANT: MSDS must be read and understood prior to use.

FS-600

FS600 Data Sheet 2013



Quin Global Pty Ltd
30 Faunce St Queanbeyan NSW 2620
Tel: 02 6175 0574
www.quinglobal.com

