Sikabond[®] T55J



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	29.04.2022	00000601639	Date of first issue: 29.04.2022

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Sikabond® T55J

Product code

: 000000601639

Manufacturer or supplier's details

Company	: Sika Australia Pty. Ltd. 55 Elizabeth Street
	Wetherill Park, NSW 2164
Telephone	: +61 2 9725 11 45
Telefax	: +61 2 9725 33 30
Emergency telephone num- ber	: +61 1800 033 111
Recommended use of the c	hemical and restrictions on use

Product use	: Adhesive
-------------	------------

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification Flammable liquids	:	Category 4
Specific target organ toxicity - repeated exposure (Inhalation)	:	Category 2 (Central nervous system)
Short-term (acute) aquatic hazard	:	Category 3
Long-term (chronic) aquatic hazard	:	Category 3
GHS label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	:	H227 Combustible liquid. H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	Prevention:
		P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
		1/9

Sikabond[®] T55J



Version 1.0	Revision Date: 29.04.2022	SDS Number: 00000601639	Date of last issue: - Date of first issue: 29.04.2022
		P260 Do not breathe mist of P273 Avoid release to the P280 Wear protective glov tion/ face protection/ hearing	environment. res/ protective clothing/ eye protec-
		Response: P314 Get medical advice/ a P370 + P378 In case of fire alcohol-resistant foam to e	e: Use dry sand, dry chemical or
		Storage: P403 Store in a well-ventila	ated place.
		Disposal: P501 Dispose of contents/ disposal plant.	container to an approved waste

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Hydrocarbons, C9-C12, n-alkanes, isoalkanes,	64742-82-1	>= 2.5 -< 10
cyclics, aromatics (2-25%)		
aromatic polyisocyanate	53317-61-6	0 -< 1
4,4'-methylenediphenyl diisocyanate	101-68-8	0 -< 1

SECTION 4. FIRST AID MEASURES

General advice	:	Move out of dangerous area. Consult a physician. Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air.
In case of skin contact	:	Take off contaminated clothing and shoes immediately. Wash off with soap and plenty of water.
In case of eye contact	:	Remove contact lenses. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
If swallowed	:	Clean mouth with water and drink afterwards plenty of water. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person.
Most important symptoms and effects, both acute and	:	No known significant effects or hazards. See Section 11 for more detailed information on health effects

Sikabond[®] T55J



Versio 1.0	on	Revision Date: 29.04.2022		SDS Number: 000000601639	Date of last issue: - Date of first issue: 29.04.2022
delayed			and symptoms. May cause damage to organs thro exposure if inhaled.	ough prolonged or repeated	
Notes to physician		:	Treat symptomatically.		
SECTION 5. FIREFIGHTING MEASU			SU	RES	
	Suitable	extinguishing media	:	Carbon dioxide (CO2)	
	Unsuitab media	le extinguishing	:	Water	
	Hazardou ucts	us combustion prod-	:	No hazardous combustion product	ts are known
	Specific e ods	extinguishing meth-	:	Standard procedure for chemical f	ires.
	Special p for firefig		:	In the event of fire, wear self-conta	ained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : tive equipment and emer- gency procedures	Use personal protective equipment. Deny access to unprotected persons.
Environmental precautions :	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for : containment and cleaning up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion	:	Normal measures for preventive fire protection.
Advice on safe handling	:	Avoid exceeding the given occupational exposure limits (see section 8). For personal protection see section 8. Smoking, eating and drinking should be prohibited in the ap- plication area. Follow standard hygiene measures when handling chemical products
Hygiene measures	:	Handle in accordance with good industrial hygiene and safety
		3/9

Sikabond[®] T55J



Version 1.0	Revision Date: 29.04.2022	SDS Number: 000000601639	Date of last issue: - Date of first issue: 29.04.2022	
		practice. When using do not eat or drink. When using do not smoke. Wash hands before breaks and at the end of workday.		
Conditions for safe storage		 Store in original container. Keep in a well-ventilated place. Observe label precautions. Store in accordance with local regulations. 		

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace	control parame	ters				
Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis		
Hydrocarbons, C9-C12, n- alkanes, isoalkanes, cyclics, aromatics (2-25%)	64742-82-1	TWA	900 mg/m3	AU OEL		
4,4'-methylenediphenyl diiso- cyanate	101-68-8	TWA	0.02 mg/m3 (NCO)	AU OEL		
	Further inform cinogen, Sens		2 (Carc. 2) Suspecte	d human car-		
		STEL	0.07 mg/m3 (NCO)	AU OEL		
Appropriate engineering controls	: Use adequate ventilation and/or engineering controls to pre- vent exposure to vapours.					
Personal protective equipment						
Respiratory protection	In case of inadequate ventilation wear respiratory protection. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.					
Hand protection	approved sta chemical pro essary. Follow AS/N Recommend	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is nec- essary. Follow AS/NZS 1337.1 Recommended: Butyl rubber/nitrile rubber gloves. Contaminated gloves should be removed.				
Eye protection	: Safety glasse	es				
Skin and body protection	Protective clothing (e.g. safety shoes, long-sleeved working clothing, long trousers) Follow AS 2210:3 Protective clothing needs to be made of cotton.					

Components with workplace control parameters

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Sikabond[®] T55J



Version 1.0	Revision Date: 29.04.2022		SDS Number: 000000601639	Date of last issue: - Date of first issue: 29.04.2022
Appea	arance	:	paste	
Colou	ır	:	light brown	
Odou	r	:	characteristic	
Odou	r Threshold	:	No data available	
pН		:	Not applicable	
	ng point/range / Freezing	:	No data available	
point Boilin	g point/boiling range	:	No data available	
Flash	point	:	69 °C (156 °F) (Method: closed cup)	
Evapo	oration rate	:	No data available	
Flamr	mability (solid, gas)	:	No data available	
	r explosion limit / Upper nability limit	:	No data available	
	r explosion limit / Lower nability limit	:	No data available	
Vapo	ur pressure	:	0.01 hPa	
Relati	ive vapour density	:	No data available	
Densi	ity	:	ca. 1.36 g/cm3 (23 °C (73 °F))	
	ility(ies) ater solubility	:	insoluble	
Sc	olubility in other solvents	:	No data available	
	ion coefficient: n- ol/water	:	No data available	
	ignition temperature	:	No data available	
Deco	mposition temperature	:	No data available	
Visco Vis	sity scosity, dynamic	:	No data available	
Vis	scosity, kinematic	:	> 20.5 mm2/s (40 °C (104 °F))	
Explo	sive properties	:	No data available	
Oxidiz	zing properties	:	No data available	

Sikabond[®] T55J



Version 1.0	Revision Date: 29.04.2022		SDS Number: 000000601639	Date of last issue: - Date of first issue: 29.04.2022
Vola	Volatile organic compounds		Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 3.85% w/w	
SECTION	N 10. STABILITY AND RE	AC	ΤΙVΙΤΥ	
Rea	Reactivity		No dangerous reaction knowr	n under conditions of normal use.
Che	Chemical stability		The product is chemically stable.	
	Possibility of hazardous reac- : No hazards to be specially mentioned. tions		entioned.	
Con	ditions to avoid	:	No data available	
Inco	mpatible materials	:	: see section 7.	

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components: aromatic polyisocyanate: Acute oral toxicity :	LD50 Oral (Rat): > 5,000 mg/kg
Acute of al toxicity .	$ED50 Oral (Rat) > 5,000 \mathrm{Hg/kg}$
4,4'-methylenediphenyl diisoc Acute oral toxicity :	yanate: LD50 Oral (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity :	LC50: 1.5 mg/l Exposure time: 4 h Test atmosphere: dust/mist Method: Expert judgement

Skin corrosion/irritation

Not classified based on available information.

Components:

Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%): Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Not classified based on available information.

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Sikabond[®] T55J



Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	29.04.2022	00000601639	Date of first issue: 29.04.2022

Respiratory sensitisation

Not classified based on available information.

Chronic toxicity

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity No data available	
Persistence and degradability No data available	
Bioaccumulative potential No data available	
Mobility in soil No data available	
Other adverse effects	
<u>Product:</u> Additional ecological infor- : mation	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	The product should not be allowed to enter drains, water courses or the soil. Do not contaminate ponds, waterways or ditches with chemi- cal or used container.

Sikabond[®] T55J



Version 1.0	Revision Date: 29.04.2022	SDS Number: 000000601639	Date of last issue: - Date of first issue: 29.04.2022
		Send to a licensed waste	e management company.
Contaminated packaging		: Empty remaining conten Dispose of as unused pr Do not re-use empty con Do not burn, or use a cut	oduct.

If potential for exposure exists refer to Section 8 for specific personal protective equipment.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR Not regulated as a dangerous good

IMDG-Code Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable for product as supplied.

National Regulations

ADG Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform : No poison schedule Scheduling of Medicines and Poisons	number allocated
International Chemical Weapons Convention (CWC) Schedules of Toxic Chemicals and Precursors Prohibition/Licensing Requirements	 Not applicable There is no applicable prohibition, authorisation and restricted use requirements, including for carcino- gens referred to in Schedule 10 of the model WHS Act and Regula- tions.

The components of this product are reported in the following inventories:

AIIC : On the inventory, or in compliance with the inventory

SECTION 16. OTHER INFORMATION

Sikabond[®] T55J



Versi 1.0	ion	Revision Date: 29.04.2022		SDS Number: 000000601639	Date of last issue: - Date of first issue: 29.04.2022
	Revision Date form		:	29.04.2022 dd.mm.yyyy	
	Full text	of other abbreviatio	ons		
	AU OEL		:	Australia. Workplace Exposure St taminants.	andards for Airborne Con-
	AU OEL / AU OEL / ADG		:	Exposure standard - time weighte Exposure standard - short term ex Australian Dangerous Goods Cod	kposure limit
	ADR		:	European Agreement concerning Dangerous Goods by Road	
	CAS DNEL EC50		:	Chemical Abstracts Service Derived no-effect level Half maximal effective concentration	
	GHS IATA		:	Globally Harmonized System International Air Transport Association	
	IMDG LD50		:	 International Maritime Code for Dangerous Goods Median lethal dosis (the amount of a material, given all at once, which causes the death of 50% (one half) of a group of test animals) 	
	LC50		:	Median lethal concentration (concentrations of the chemical in air that kills 50% of the test animals during the observation period)	
	MARPOL		:	International Convention for the P Ships, 1973 as modified by the Pr	
	OEL PBT		:	Occupational Exposure Limit Persistent, bioaccumulative and to	
	PNEC REACH		:	Predicted no effect concentration Regulation (EC) No 1907/2006 of and of the Council of 18 December istration, Evaluation, Authorisation cals (REACH), establishing a Euro	er 2006 concerning the Reg- and Restriction of Chemi-
	SVHC vPvB		:	Substances of Very High Concern Very persistent and very bioaccun	l

Safety Data Sheets are updated frequently. Please ensure that you have a current copy. SDS may be obtained from the following website: aus.sika.com

The information contained in this Safety Data Sheet corresponds to our level of knowledge at the time of publication. All warranties are excluded. Our most current General Sales Conditions shall apply. Please consult the product data sheet prior to any use and processing.

Changes as compared to previous version !

AU / EN