

ALSAN FLEECE 165 B

TECHNICAL DATA SHEET

ANZ-TDS-93-ALSAN FLEECE 165 B



ACCESSORY
PRODUCTS

APPLICATIONS

ROOFS

FOUNDATIONS

GREEN ROOFS

DESCRIPTION

ALSAN FLEECE 165 B is a non-woven polyester fleece specially designed to use with the ALSAN FLASHING QUADRO waterproofing resin.

ALSAN FLEECE 165 B is used as reinforcement and ensures that a minimum layer thickness of the ALSAN FLASHING QUADRO waterproofing resin must be applied.

The combination provides a high-quality flexible and crack-bridging waterproofing system.

APPLICATION

- Apply the **ALSAN FLEECE 165 B** on top of the 2/3 of the resin wet in place, then install the last 1/3 of the resin on top.
- The **ALSAN FLEECE 165 B** overlap must be at least 50 mm. Resin must be applied between the overlaps.



FOR COMPLETE INFORMATION ON PRODUCT INSTALLATION, PLEASE CONSULT YOUR SOPREMA REPRESENTATIVE.

PACKAGING & PROPERTIES

SPECIFICATIONS	TEST METHOD	ALSAN FLEECE 165 B
Density	-	165 g/m ²
Thickness	-	0,92 mm
Colour	-	White
Width	-	150 / 200 / 260 / 350 / 1050 mm
Length	-	50 m
Tear resistance	ISO 527-3	350 / 330 N
Elongation at break	ISO 527-3	49 / 62 %

STORAGE AND HANDLING

Store in a dry place protected from moisture and pollution.

STATEMENT OF RESPONSIBILITY

The technical information and application advice given in this publication is based on the present state of our best knowledge. As the information herein is of a general nature, no assumption can be made as to a product's suitability for a particular use or application and no warranty as to its accuracy, reliability or completeness either expressed or implied is given other than those required by Commonwealth or State Legislation. The owner, their representative and/or the contractor are responsible for checking the suitability of products for their intended use.



SOPREMA.COM.AU • +61 (3) 9221 6230

1/1