

PRODUCT INFORMATION

DESCRIPTION

The PVC FLAGMETAL SHEET is made of galvanized steel coupled with FLAGON PVC membrane.

USE

The PVC FLAGMETAL SHEET is used for the realization of flashings or profiles made to size for use in roofing as finishing elements in waterproofing systems realized with FLAGON PVC synthetic membranes.

APPLICATION METHOD

The PVC FLAGMETAL SHEET is fixed with screws.

The Flagon PVC membrane is welded with Leister hot air gun over the entire length of the PVC Flagmetal Sheet.



CHARACTERISTIC

- Resistant to weathering and UV

CHARACTERISTIC

DEVELOPMENT

Width	-	1 m
Length	-	2 m / 3 m
Total thickness	-	1,80 mm
- metal sheet thickness	-	0,60 mm
- PVC membrane thickness	-	1,20 mm



STORAGE AND PACKAGING

Weight	6 kg/m ²
Length	2 m / 3 m
Color	grey

NOTE

Laying by installer approved by Soprema srl.

UNI EN ISO 9001:2000 (Quality Company System) and UNI EN ISO 14001 (environmental system) certified quality system.

The data herewith indicated are not exhaustive and Soprema srl may modify them without previous notice. Soprema srl, has the right to modify the product at any time and without previous notice, in any of its aspect, and to stop its production. In case of dispute the official version of this sheet product information will be provided directly by the technical office Soprema srl stamped and signed by the technical manager. Soprema srl reserves the right, as technology and know-how progress, to modify without warning the composition and conditions of use of its materials, and subsequently their price. As a result, orders shall only be accepted on the basis of the terms and technical specifications applicable at the time of receipt.